

Supporting Information

Centroid Molecular Dynamics Can Be Greatly Accelerated Through Neural Network Learned Centroid Forces Derived from Path Integral Molecular Dynamics

Timothy D. Loose, Patrick G. Sahrman, and Gregory A. Voth*

Department of Chemistry, Chicago Center for Theoretical Chemistry, James Franck Institute, and Institute for Biophysical Dynamics, The University of Chicago, Chicago, IL 60637, USA

*Corresponding Author: gavoth@uchicago.edu

```

{
  "_comment": "para-hydrogen model parameters",
  "model": {
    "_comment": " H will be 0 consistent with type.raw ",
    "type_map": ["H"],
    "descriptor" :{
      "type": "se_e2_a",
      "sel": [46],
      "rcut_smth": 1.00,
      "rcut": 6.00,
      "neuron": [10, 20, 40],
      "resnet_dt": false,
      "seed": 1,
      "_comment": " that's all"
    },
    "fitting_net" : {
      "neuron": [240, 240, 240],
      "resnet_dt": true,
      "seed": 1,
      "_comment": " that's all"
    },
    "_comment": " that's all"
  },
  "learning_rate" :{
    "type": "exp",
    "decay_steps": 5000,
    "start_lr": 0.005,
    "stop_lr": 1.76e-7,
    "_comment": "that's all"
  },
  "loss" :{
    "start_pref_e": 0,
    "limit_pref_e": 0,
    "start_pref_f": 1000,
    "limit_pref_f": 1000,
    "start_pref_v": 0,
    "limit_pref_v": 0,
    "_comment": " that's all"
  },
  "_comment": " traing controls",
  "training" : {
    "systems": ["../data/"],
    "set_prefix": "set",
    "stop_batch": 500000,
    "batch_size": [1],

    "seed": 1,

    "_comment": " display and restart",
    "_comment": " frequencies counted in batch",
    "disp_file": "lcurve.out",
    "disp_freq": 100,
    "numb_test": 10,
    "save_freq": 500,
    "save_ckpt": "model.ckpt",
    "disp_training": true,
    "time_training": true,
    "profiling": false,
    "profiling_file": "timeline.json",
    "_comment": "that's all"
  },
}

```

```
}  "_comment":      "that's all"
```

```

{
  "_comment": "water model parameters",
  "model": {
    "_comment": " H and O will be 0 and 1, consistent with type.raw ",
    "type_map": ["H", "O"],
    "descriptor" :{
      "type":      "se_e2_a",
      "sel":       [60, 30],
      "rcut_smth": 1.00,
      "rcut":      6.00,
      "neuron":    [10, 20, 40],
      "resnet_dt": false,
      "seed":      1,
      "_comment": " that's all"
    },
    "fitting_net" : {
      "neuron":    [240, 240, 240],
      "resnet_dt": true,
      "seed":      1,
      "_comment":  " that's all"
    },
    "_comment": " that's all"
  },
  "learning_rate" :{
    "type":      "exp",
    "decay_steps": 5000,
    "start_lr":  0.005,
    "stop_lr":   1.76e-7,
    "_comment": "that's all"
  },
  "loss" :{
    "start_pref_e": 0,
    "limit_pref_e": 0,
    "start_pref_f": 1000,
    "limit_pref_f": 1000,
    "start_pref_v": 0,
    "limit_pref_v": 0,
    "_comment": " that's all"
  },
  "_comment": " traing controls",
  "training" : {
    "systems": ["../data/"],
    "set_prefix": "set",
    "stop_batch": 100000,
    "batch_size": [10],

    "seed":      1,

    "_comment": " display and restart",
    "_comment": " frequencies counted in batch",
    "disp_file": "lcurve.out",
    "disp_freq": 100,
    "numb_test": 10,
    "save_freq": 500,
    "save_ckpt": "model.ckpt",
    "disp_training":true,
    "time_training":true,
    "profiling":    false,
    "profiling_file":"timeline.json",
    "_comment": "that's all"
  },
},

```

```
}  "_comment":      "that's all"
```